



SOFFIT INSTALLATION GENERAL NOTES:

- A. THICKNESS SHALL BE COORDINATED WITH PROJECT REQUIREMENTS BASED ON ENGINEERING OF TERREAL TERRACOTTA RAINSCREEN SYSTEM AND THERMAL ENVELOPE REQUIREMENTS.
- B. RIGID INSULATION INDICATED MAY BE MINERAL WOOL OR NFPA 285 COMPLIANT RIGID FOAM.
- C. CONSULT WITH TERREAL NORTH AMERICA ON SOFFIT INSTALLATION CONDITIONS TO DETERMINE IF INTERMEDIATE CORE SUPPORT MEMBERS ARE RECOMMENDED.



P.O. BOX 309 New Lexington, Ohio 43764
 Telephone: (888) 582-9052 Fax: (740) 342-1906
 www.terrealna.com

SYSTEM:	PITERAK SLIM
DETAIL #:	PS-303-f
Description:	SOFFIT INTERIOR CORNER SECTION
Building Construction:	COLD-FORMED METAL STUD
Drawing Date:	2018.11.26
Scale:	3" = 1'-0"
Terreal N.A. Reference #:	PITERAK SLIM PS-303-f.

The information contained on this drawing is the confidential property of Terreal North America, LLC. Any use or reproduction in whole or in part without the express written permission of Terreal North America, LLC is strictly prohibited. Terreal North America, LLC reserves the right to modify the configuration of item(s) shown without prior written notice.